



FIBRE GLAST DEVELOPMENTS CORP.
385 CARR DRIVE
BROOKVILLE, OH 45309
Rev 04/11

TELEPHONE: (937) 833-5200
FAX: (937) 833-6555
**FOR CHEMICAL EMERGENCY
CALL (800) 424-9300 24 HRS.**

SECTION 1 - PRODUCT IDENTIFICATION

PART #580 Yellow Sealant Tape

CHEMICAL NAME AND SYNONYMS: Sealant Tape

TRADE NAME: GS-AT-200Y

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS Components (Specific Chemical Identity: Common Name(s)):
OSHA PEL

ACGIH TLV

Other Limits Recommended

% (optional)

This product is considered non-hazardous, non-combustible and non-explosive.

SECTION 3 - PHYSICAL DATA

BOILING POINT: Not applicable

VAPOR PRESSURE (mm Hg.): Not applicable

VAPOR DENSITY (AIR=1): Not applicable

SOLUBILITY IN WATER: Insoluble

APPEARANCE AND ODOR: Yellow, Pliable, Rubbery Sealant – No odor

SPECIFIC GRAVITY (H₂O=1): 1.380

MELTING POINT: Not applicable

EVAPORATING RATE (Butyl Acetate=1): Not applicable

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): 600°F (315°C)

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, or Water.

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool fire exposed surfaces and isolate fuel supply. Recommend using a breathing apparatus and protective goggles.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This product is non-explosive. A fire may produce carbon monoxide and irritation smoke.

FLAMMABLE LIMITS: N/A

LEL:

UEL:

SECTION 5 - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: None

INCOMPATIBILITY (Material to Avoid): Oxidizers, Oxidizing Agents

HAZARDOUS DECOMPOSITION OR BY PRODUCT: Fire is accompanied by evolving of carbon monoxide, carbon dioxide and hydrocarbon gases

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

SECTION 6 - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY

INHALATION: No

SKIN: No

INGESTION: No

HEALTH HAZARDS (Acute and Chronic): None

CARCINOGENICITY

NTP: No

IARC MONOGRAPHS: No

OSHA REGULATED: No

SIGNS AND SYMPTOMS OF EXPOSURE: Not Applicable

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Not Applicable

EMERGENCY AND FIRST AID PROCEDURES: Not Applicable

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Recover spilled material and place in appropriate marked container for reuse or disposal.

WASTE DISPOSAL METHOD: Waste material may be disposed of under conditions which meet federal, state, and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store at 72° F (22°C)

OTHER PRECAUTIONS: Do not take internally it is for industrial use only.

SECTION 8 – CONTROL MEASURES

RESPIRATORY PROTECTION (Specific Type): None

VENTILATION: Not Normally Required

Local Exhaust: None

Mechanical (General): None

Special: None

Other: None

Eye Protection: None

PROTECTIVE GLOVES: Recommended when material is hot

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None

WORK/HYGRENIC PRACTICES: None

SECTION 9 - COMMENTS

The information accumulated herein is believed to be accurate but is not warranted to be, whether originating with Fibre Glast Developments or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.